

RANDOLPH COUNTY COMMISSION
WEDOWEE, ALABAMA

INVITATION FOR BIDS
(UP TO 4 UNITS)

In accordance with the bid laws of the State of Alabama, notice is hereby given that the Randolph County Commission will receive competitive bids on the following items:

ROTARY CUTTERS FLEX WING TYPE

**SEE ATTACHED SPECIFICATIONS

F.O.B. _____ Date of Delivery _____ Terms _____

You are invited to bid on the above items. Any substitutes offered must be submitted in detail. The right to reject any items or materials not of quality or under any provisions of this act is reserved. Bids may be mailed to Randolph County Commission, PO Box 228, Wedowee, AL 36278 or delivered to our office located in the Walker Building Courthouse Annex, 12 Broad Street East, Wedowee, AL 36278. Our phone number is (256) 357-4980.

Bids will be opened on Thursday the 27th day of February 2025 at 2:00 p.m. All bids must be sealed and the word "BID" and name of item marked on outside of envelope. If you do not wish to submit a bid, please submit a "no bid" reply.

The Randolph County Commission Reserves The Right To Reject Any And All Bids

Company Name

Randolph County Commission
Chairman

Company Representative

Date

**SPECIFICATIONS
ROTARY CUTTERS FLEX WING TYPE**

Cutting Width:	-15 feet with two wings -14 feet with one wing - 10 feet with one wing
Cutting Height:	2 inches to 14 inches
Transport Width:	96 inches
Hitch:	Floating type, draw bar pull type with jack stand
Safety Chains:	Highway type double row
Tires:	(6) 15 inch diameter used aircraft non-recapped foam filled
Hydraulics:	Hoses and hook-up connectors supplied to connect to John Deere 5100M tractors currently owned by Randolph County. Left & right wing or right wing to be hydraulically raised from tractor with normal operation from +85 degrees to -24 degrees.
Blades:	½ inch x 4 inch heat treated blades mounted on round skid pans with 6 inch overlap
Gear Boxes:	Three mechanical P.T.O. 540 rpm with tapered roller bearings. Power divider gear box rating 235 hp min. Wing gearbox rating 205 hp min.
Power Train:	Main driveline Cat. 5 min. ‘CV’ type with safety covers. Wing drive lines Cat. 4 min. with skid clutches and safety covers.
Main Frame:	7 gauge minimum thickness deck, replaceable adjustable side skirts ¼ thick with replaceable skid shoes. Center deck section to have a smooth deck design (no ribs) for easy cleaning. Underside deck rings require at all cutters (3).
Linkage:	Main cutter section to have self leveling adjustable linkage with hydraulic over-ride.
Warranty:	State warranties.
Manual:	One set of parts and service manuals

Please state delivery date and any other substitutions in writing as a part of your bid. Further questions should be directed to Justin Rush, County Engineer, 256 357 2311